Index

/

/usr/include/X11/bitmaps, 9
/usr/lib/X11/app-defaults, 14

A

A, note, **4**
app-defaults, 14
application defaults, 14
application header file, **4**
application programmer, **2**
Arg, **16**
ArgList, **16**
argument lists, **16**
AsciiSink object, 86, **93**, 95
  class name, 93
  resources, 94, 102
AsciiSink.h, 93
asciiSinkObjectClass, 93
AsciiSinkP.h, 93
AsciiSrc object, 86, **90**, 95
  class name, 90
  resources, 91
AsciiSrc.h, 90
asciiSrcObjectClass, 90
AsciiSrcP.h, 90
AsciiText widget, **85**, 95
  class name, 85
  resources, 86
AsciiText.h, 85
AsciiTextP.h, 85
asciiTextWidgetClass, 85

B

bitmap conversions, **9**
BitmapFilePath, **9**
bitmapFilePath, **9**
Box widget, **107**
  class name, 107
  layout semantics, 109
  resources, 108, 125
Box.h, 107, 125
BoxP.h, 107
boxWidgetClass, 107
ButtonPress, 136

C

C, note, **4**
CallbackProc, **12**
callbacks, 12
chapter format, **4**
child, 2
class header file, **4**
class name, **4**
class, **2**, **4**
client, **2**
Command widget, **18**
  actions, 21
  class name, 18
  resources, 19
  translation bindings, 22
Command.h, 18
CommandP.h, 18
commandWidgetClass, 18
compiling applications, 14
conventions:
  chapter format, **4**
  used in manual, **3**
conversions, **8**
  AsciiType, 90, 92
  BackingStore, 59
  Bitmap, **9**
  ColorCursor, **9**
  Cursor, **9**
  Gravity, 126
  Justify, 21, 27, 39, 53, 68
  Orientation, 43, 109, 120
  Pixel, **9**
  ShapeStyle, 21, 40, 54, 69
  Widget, 112, 116
  XawTextEditType, 88, 92, 99
  XawTextResizeMode, 89, 97
  XawTextScrollMode, 89, 97
Core widget, 131
creating new widgets, **131**
creating widgets, **7**
cursor, 9

D

D, note, **4**
destroyCallback, **13**

Dialog widget, 107, **109**
  automatically created children, 113
  class name, 110
  constraint resources, 111
  layout semantics, 112
  resources, 110
  special considerations, 113
Dialog.h, 109
DialogP.h, 110
dialogWidgetClass, 110

E

events, 10
examples, 17

F

fallback resources, **6**
FindPosition, 104
float resources:
  setting, 45
FMT8BIT, 82
Form widget, 107, **114**
  class name, 114
  constraint resources, 115
  re-layout, 117
  resources, 114
Form.h, 114
FormP.h, 114
formWidgetClass, 114
fromHoriz, 112, 116
fromLeft, 113
fromVert, 112, 116
FullName, 2

G

geometry management, 107
Grip widget, 18, **22**
  actions, 24
  class name, 22
  GripAction routine, 24
  GripAction table, 25
  resources, 23
Grip.h, 22
GripAction, 122
GripCallData, 25
GripP.h, 22
gripWidgetClass, 22

H

horizDistance, 112, 116

I

initialization, **6**
input focus, **5**
Input Method, 79
input, **5**
instance, **2**
internationalization, 6
Intrinsic.h, 13
introduction, **1**

J

jumpProc, **44**

K

KeyPress, 136

L

Label widget, 18, **25**
  class name, 25
  resources, 25
Label.h, 25
LabelP.h, 25
labelWidgetClass, 25
libICE, 14
libSM, 14
libX11, 14
libXaw, 14
libXext, 14
libXmu, 14
libXt, 14
linking applications, 14
List widget, 18, **28**
  actions, 31
  callbacks, 31
  class name, 28
  default translation table, 31
  resources, 28
List.h, 28
ListP.h, 28
listWidgetClass, 28

locale, 6

M

MenuButton widget, **66**
  actions, 69
  class name, 66
  resources, 66
MenuButton.h, 66
MenuButtonP.h, 66
menuButtonWidgetClass, 66
Menus, 57
  popup, 57
  pulldown, 57
  using, 57
method, **2**
MultiSink object, 86, 95
MultiSrc object, 86, 95

N

name:
  widget, **2**
notes, **4**

O

object, **2**

P

Paned widget, 107, **117**
  change height settings, 122
  class name, 117
  constraint resources, 120
  disable auto-reconfiguring, 123
  disable pane resizing, 122
  enable auto-reconfiguring, 123
  enable pane resizing, 122
  get height settings, 123
  getting the number of children, 123
  layout semantics, 121
  resources, 118
  using, 117
Paned.h, 117
PanedP.h, 117
panedWidgetClass, 117
Panner widget, 18, **33**
  actions, 35
  callbacks, 36
  class name, 33
  default translation table, 36
  resources, 33
Panner.h, 33
PannerP.h, 33
pannerWidgetClass, 33
parent, **2**
pixel, 9
Porthole widget, 107, **123**
  callbacks, 125
  class name, 123
  layout semantics, 125
  resources, 123
Porthole.h, 123
PortholeP.h, 123
portholeWidgetClass, 123

R

R, note, **4**
Radio button, 51
Radio groups, 51, 55
  one of many, 55
  zero or one of many, 55
radioData, 56
realizing widgets, **9**
Repeater widget, 18, **36**
  actions, 40
  class name, 36
  resources, 37
  translation bindings, 40
Repeater.h, 36
RepeaterP.h, 36
repeaterWidgetClass, 36
ReportProc, **36**, **125**
resource, **2**, 8, 14
rgb.txt, 9

S

Scrollbar widget, 18, **40**
  actions, 44
  callbacks, 44
  class name, 40
  default translation table, 44
  resources, 41
  setting thumb values, 45
Scrollbar.h, 40
ScrollbarP.h, 40
scrollbarWidgetClass, 40
ScrollProc, **44**
SetSelection, **101**
Simple widget, 18, **46**
  class name, 46
  resources, 46
simple widgets, 18

Simple.h, 46
SimpleMenP.h, 58
SimpleMenu widget, **57**
  actions, 60
  class name, 58
  default translations, 60
  MenuPopdown routine, 60, 61
  positioning, **61**
  resources, 58
SimpleMenu.h, 57
simpleMenuWidgetClass, 58
SimpleP.h, 46
simpleWidgetClass, 46
Sme object, 57, **64**
  class name, 65
  Highlight method, 65
  Notify method, 65
  subclassing, 65
  Unhighlight method, 65
Sme.h, 64
SmeBSB object, 57, **62**
  class name, 62
  resources, 62
SmeBSB.h, 62
smeBSBObjectClass, 62
SmeBSBP.h, 62
SmeLine object, 57, **64**
  class name, 64
  resources, 64, 65
SmeLine.h, 64
smeLineObjectClass, 64
SmeLineP.h, 64
smeObjectClass, 64
SmeP.h, 64
string conversions, **8**
StringDefs.h, 13
StripCharP.h, 48
StripChart widget, 18, **48**
  class name, 48
  getting the value, 50
  getValue callback, **50**
  resources, 48
StripChart.h, 48
stripChartWidgetClass, 48
subclassing, **131**
superclass, **2**, 4

T

Text widget, 94, **95**
  actions, **74**
  class name, 95
  ConvertSelection, **101**
  customizing, **94**
  default key bindings, 71
  default translations, 80
  edit modes, 71
  file insertion, 73
  query replace, 72
  resources, 95
  search, 72
  Text Selections for Application Programmers, 79
  Text Selections for Users, 74
  User’s Guide to the Text widget, 71
Text.h, 95
TextP.h, 95
TextSink object, 94, **101**
  class name, 102
  ClearToBackground, **103**
  DisplayText, **102**
  FindDistance, **104**
  FindPosition, **103**
  GetCursorBounds, **106**
  InsertCursor, **103**
  MaxHeight, **105**
  MaxLines, **105**
  Resolve, **104**
  SetTabs, **105**
  subclassing, **102**
TextSink.h, 101
textSinkObjectClass, 102
TextSinkP.h, 101
TextSrc object, 95, **98**
  class name, 98
  Read, **99**
  Replace, **99**
  resources, 98
  Scan, **100**
  Search, **100**
  subclassing, **99**
TextSrc.h, 98
textSrcObjectClass, 98
TextSrcP.h, 98
textWidgetClass, 95
Toggle widget, 18, **50**
  actions, 54
  class name, 50
  default translation table, 54
  resources, 51
  used in radio groups, 51
Toggle.h, 50
ToggleP.h, 50
toggleWidgetClass, 50
toolkit initialization, **6**
Tree widget, 107, **125**
  class name, 125

constraint resources, 127
convenience routines, 127
layout semantics, 127
TreeP.h, 125
treeWidgetClass, 125
type conversions, **8**

U

underlying model, **3**
user, **2**
using widgets, **6**

V

vertDistance, 112, 116
Viewport widget, 107, **128**
class name, 128
layout semantics, 130
resources, 128
Viewport.h, 128
ViewportP.h, 128
viewportWidgetClass, 128

W

widget class, **3**
widget creation, **7**
widget programmer, **3**
widget, **3**
widgetClass, 131
Window widget, 131
WrapMode, 90, 98
writing applications, 13

X

X11/Intrinsic.h, 13
X11/Xaw/Command.h, 13
X11/Xaw/Label.h, 13
X11/Xaw/Template.c, 132, 134
X11/Xaw/Template.h, 132
X11/Xaw/TemplateP.h, 132, 133
X11/Xlib.h, 13
XawAsciiSave, **93**
XawAsciiSaveAsFile, **93**
XawAsciiSourceChanged, **93**
XawAsciiSourceFreeString, **93**, 113
XawChain, 112, 116
XawChainBottom, 112, 116
XawChainLeft, 112, 116
XawChainRight, 112, 116
XawChainTop, 112, 116
XawDialogAddButton, **113**
XawDialogGetValueString, **113**
XawEdgeType, 111, 115
XawEditDone, 83, 100
XawEditError, 83, 100
XawFormDoLayout, **117**
XawGripCallData, **24**, 25
XawGripCallDataRec, **24**, 25
XawListChange, **31**, 32
XawListHighlight, **32**
XawListReturnStruct, **31**, 32
XawListShowCurrent, **32**
XawListUnhighlight, **32**
XawPanedAllowResize, **122**
XawPanedGetMinMax, **123**
XawPanedGetNumSub, **123**
XawPanedSetMinMax, **122**
XawPanedSetRefigureMode, **123**
XawPositionError, 83, 100
XawPositionSimpleMenu, **61**
XawRubber, 111, 112, 115, 116
XawScrollbarSetThumb, **45**
XawScrollbarThumb, 45
XawsdLeft, 100
XawsdRight, 100
XawselectAll, 79
XawselectChar, 79
XawselectLine, 79
XawselectNull, 79
XawselectParagraph, 79
XawselectPosition, 79
XawselectWord, 79
XawSimpleMenuAddGlobalActions, **61**
XawSimpleMenuClearActiveEntry, **62**
XawSimpleMenuGetActiveEntry, **61**
XawstAll, 100
XawstEOL, 100
XawstParagraph, 100
XawstPositions, 100
XawstWhiteSpace, 100
XawtextAppend, 88, 92, 99
XawTextBlock, **81**
XawTextBlockPtr, 81
XawTextDisableRedisplay, **84**
XawTextDisplay, **84**
XawTextDisplayCaret, **85**
XawtextEdit, 88, 92, 99
XawTextEnableRedisplay, **83**
XawTextGetInsertionPoint, **85**
XawTextGetSelectionPos, **82**
XawTextGetSource, **85**
XawTextInvalidate, **83**
XawTextPosition, **81**

XawtextRead, 88, 92, 99
XawTextReplace, 71, **82**
XawtextResizeBoth, 89, 97
XawtextResizeHeight, 89, 97
XawtextResizeNever, 89, 97
XawtextResizeWidth, 89, 97
XawtextScrollAlways, 89, 97
XawtextScrollNever, 89, 97
XawtextScrollWhenNeeded, 89, 97
XawTextSearch, **83**
XawTextSearchError, 101
XawTextSetInsertionPoint, **84**
XawTextSetSelection, **82**
XawTextSetSelectionArray, 79, **84**
XawTextSetSource, **85**
XawTextSinkClearToBackground, 102
XawTextSinkDisplayText, 102
XawTextSinkFindDistance, 102
XawTextSinkFindPosition, 102
XawTextSinkGetCursorBounds, 102
XawTextSinkInsertCursor, 102
XawTextSinkMaxHeight, 102
XawTextSinkMaxLines, 102
XawTextSinkResolve, 102
XawTextSinkSetTabs, 102
XawTextSourceConvertSelection, 99
XawTextSourceRead, 99
XawTextSourceReplace, 99
XawTextSourceScan, 99
XawTextSourceSearch, 99
XawTextSourceSetSelection, 99
XawTextTopPosition, 84
XawTextUnsetSelection, **82**
XawtextWrapLine, 90, 98
XawtextWrapNever, 90, 98
XawtextWrapWord, 90, 98
XawToggleChangeRadioGroup, **55**
XawToggleGetCurrent, **56**
XawToggleSetCurrent, **56**
XawToggleUnsetCurrent, **56**
XawTreeForceLayout, **127**
XawWMProtocols, 79
XAW_LIST_NONE, 32
xrdb, 14
XrmParseCommand, 7
XtAddCallback, **12**, 13
XtAddCallbacks, 12
XtAppInitialize, **6**, 10, 13
XtAppMainLoop, **10**, 13
XtCallbackList, **12**
XtCallbackProc, 12
XtCallbackRec, **12**
XtCreateManagedWidget, **7**, 13
XtCreateWidget, 10, 12
XtDefaultBackground, 8, 9
XtDefaultForeground, 8, 9
XtDestroyWidget, **11**
XtError, 7
XtGetApplicationResources, 15
XtGetValues, **11**, 12, 137
XtInheritClearToBackground, 102, 103
XtInheritConvertSelection, 99
XtInheritDisplayText, 102
XtInheritFindDistance, 102
XtInheritFindPosition, 102
XtInheritGetCursorBounds, 102
XtInheritInsertCursor, 102
XtInheritMaxHeight, 102
XtInheritMaxLines, 102
XtInheritRead, 99
XtInheritReplace, 99
XtInheritResolve, 102
XtInheritScan, 99
XtInheritSearch, 99
XtInheritSetSelection, 99
XtInheritSetTabs, 102
XtManageChildren, **10**
XtMapWidget, **10**
XtMoveWidget, 107
XtN, **13**
XtNameToWidget, 113, 130
XtNcallback, 13
XtNinput, **5**
XtNumber, 16, 17
XtorientHorizontal, 43, **109**, 120
XtorientVertical, 43, **109**, 120
XtRealizeWidget, 7, **9**, 10, 13
XtResizeWidget, 107
XtSetArg, **16**
XtSetLanguageProc, **6**
XtSetMappedWhenManaged, **10**
XtSetValues, **11**, 12, 107, 132, 133
XtWindow, 137

_

_in_out, **3**
_return, **3**