

The `outline` package* for use with L^AT_EX 2_ε

Gerd Neugebauer
Im Lerchelsbühl 5
64521 Groß-Gerau
Germany
`gene@gerd-neugebauer.de`

2012/04/10

1 Introduction

Doug Henderson has provided some routines in METAFONT to create outlined versions of arbitrary METAFONT fonts. They can be found on the CTAN in the directory `tex-archive/fonts/cm/cmoutlines` together with some sample files which show outlined versions of a few computer modern fonts. This package provides means to use such outlined fonts in L^AT_EX 2_ε.

This package has been created for an article in "Die T_EXnische Komödie" [1]. This article contains some more details on the package and its use.

2 Usage

This file can be used as a package by placing its name in the argument of `\usepackage`. Afterwards some new commands are defined which are described below. Note that before these commands can be used a font has to be selected. This is done with the following command:

`\SetOutlineFonts` The command `\SetOutlineFonts` initializes the fonts used for the outlining macros. The first argument is a font specification as used by `\newfont`. Note that no spaces are allowed at the beginning. This font is loaded together with a font which has an `o` prepended to its name. The font specification may contain scaling instructions. Thus the following invocation is legal:

```
\SetOutlineFonts{cmbx12 scaled \magstep2}
```

This instruction requires the tfm files of the fonts `cmbx12` and `ocmbx12` to be loadable in the given sizes. The font with the prepended `o` is assumed to contain the outlined version of the font without the leading `o`.

*This file has version number v1.2, dated 2012/04/10.

`\outline` The command `\outline` typesets its argument in a box using the outlined font declared with `\SetOutlineFonts`.

`\OutLine` The command `\OutLine` typesets its third argument in a box using the outlined font declared with `\SetOutlinedFonts`. The interior of the characters is drawn in the color given as first argument. The outline is drawn in the color given as second argument. The colors can take any color names accepted by the color package. Thus

```
\OutLine{yellow}{red}{Outlined text}
```

typesets the text “Outlined text” in yellow bordered in red.

References

- [1] Gerd Neugebauer. Vor Gebrauch schütteln. *Die T_EXnische Komödie*, 3/97:26–36, October 1997.

3 Implementation

```
\RequirePackage{color}
```

`\SetOutlineFonts` The macro `\SetOutlineFonts` loads the fonts for the outline macros.

```
\newcommand\SetOutlineFonts[1]{%
  \newfont\OL@i{o#1}%
  \newfont\OL@ii{#1}%
}
```

`\outline` The macro `\outline` typesets its argument with the outline font.

```
\newcommand\outline[1]{\mbox{\OL@i #1}}
```

`\OutLine` The macro `\OutLine` typesets its argument with the outline font. The interior is filled with the color given as second argument. The color of the outline is given as third argument.

```
\newcommand\OutLine[3]{%
  \mbox{\rlap{\textcolor{#1}{\OL@ii #3}}\textcolor{#2}{\OL@i #3}}}
```

Change History

v1.0	General: First internal version. 1	rangements. 1
v1.1	General: Renaming and some rear-	dress updated. 1
		v1.2

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the definition; numbers in *roman* refer to the pages where the entry is used.

O		S	
<code>\Outline</code> <u>2</u> , <i>2</i>	<code>\SetOutlineFonts</code>	. <i>1</i> , <u>2</u>